

Temperature Control Unit

TT-108 K

The temperature control unit TT-108 K is constructed for water operation up to +90°C.



Features

- Mode of Operation: Water
- Suitable for double walled vessels
- Leakstopper Mode
- Digital flow indication to control minimum flow
- Automatic Temperature Control
- Heating Capacity (Switchable in Stages)
- Submersible Mechanical Pump

Technical Specifications

Mode of Operation	Water			
Temperature Range (°C)	25 - 90			
Heating Capacity (kW)	18	27	36	45
Switchable Stages	9/9/18	9/9/9/27	9/9/9/9/36	9/9/9/18/45
Electronic Flow Control	Yes			
Cooling Capacity	-			
Cooling Method	Direct			
Auto Off	No			

Pump Capacity

Motor (kW)	2.2
Pressure Mode (bar)	4.5 (max)
Vaccum Mode (mH ² O)	8.0 (max)
Flow Rate (l/min)	200 (max)

Others

Content of Unit (L)	28.0 (min) - 40.0 (max)
Dimension (mm) incl. Castors	18 & 27 kW - 960 (L) x 390 (W) x 1070 (H) 36 & 45 kW - 1250 (L) x 480 (W) x 1400 (H)
Weight (kg)	180
Voltages (V)	3 x 400 / 3 x 220
Frequency (Hz)	50 / 60
Colour	RAL 7001 (Silver Grey)

TOOL-TEMP

TOOL-TEMP Benelux B.V

Ambachtsweg 22, 5683 CD, Best, Nederland
Tel: +31 (0)40 22 66 922 Fax: +31 (0)40 22 65 515

www.tool-temp-benelux.nl
E-mail: info@tool-temp-benelux.nl